

Technical Specification

Model	Plate Material	Plate Dimensions, mm	Heated Area, mm	Heater Power, Watt	Max Plate Temp, °C	Stirrer Speed, rpm	Max Stirring Capacity, L	Compatible with SCT2	Control Accuracy w/ SCT2, °C	Dimensions (w x d x h), mm	Net weight, kg	Power, Watt	Electrical Supply	IP Rating	Digital Display Version
-------	----------------	----------------------	-----------------	--------------------	--------------------	--------------------	--------------------------	----------------------	------------------------------	----------------------------	----------------	-------------	-------------------	-----------	-------------------------

Hotplate Stirrers

US152	Coated Aluminium/Silicon	150 x 150	150 x 150	700	325	100 - 2000	15	Yes	±0.5	180 x 255 x 122	3.1	750	120V, 60Hz or 230V, 50Hz,	32	N
US152D	Coated Aluminium/Silicon	150 x 150	150 x 150	700	325	100 - 2000	15	Yes	±0.5	180 x 255 x 122	3.1	750	120V, 60Hz or 230V, 50Hz,	32	Y
UC152	Glass Ceramic	150 x 150	120 x 120	500	450	100 - 2000	15	Yes	±0.5	180 x 255 x 122	3.1	550	120V, 60Hz or 230V, 50Hz,	32	N
UC152D	Glass Ceramic	150 x 150	120 x 120	500	450	100 - 2000	15	Yes	±0.5	180 x 255 x 122	3.1	550	120V, 60Hz or 230V, 50Hz,	32	Y

Hotplates

US150	Coated Aluminium/Silicon	150 x 150	150 x 150	700	325	-	-	Yes	±1°C	180 x 255 x 122	2.5	700	120V, 60Hz or 230V, 50Hz,	32	-
UC150	Glass Ceramic	150 x 150	120 x 120	500	450	-	-	Yes	±1°C	180 x 255 x 122	2.5	500	120V, 60Hz or 230V, 50Hz,	32	-

Stirrers

US151	Stainless Steel	150 x 150	-	-	-	100 - 2000	15	No	-	180 x 255 x 109	2.4	50	120V, 60Hz or 230V, 50Hz,	32	-
UC151	Glass Ceramic	150 x 150	-	-	-	100 - 2000	15	No	-	180 x 255 x 109	2.4	50	120V, 60Hz or 230V, 50Hz,	32	-

US150



US151



US152



US152D



UC150



UC151



UC152



UC152D

