

**Performance
Characteristics**

Operating Range 30 to 75°C
(NOTE: Operating temperature must be at least 5 °C above ambient)

Average Uniformity @ 37°C*; +/- 0.5°C

Resolution 0.1°C

Control Sensitivity +/- 0.1°C

Recovery Time @ 37°C (door opened 30 seconds)
Model 625 2 minutes
Model 637 2 minutes
Model 650 3 minutes

*When tested per ASTM E-1292-94

Specifications

Operating Environment

Temperature Range: 10 °C to 35 °C
 Humidity Range: (Non-Condensing) 0% to 90% RH

Electrical Requirements

Model 625D
 Cat. No. 11-690-625D 120V, 60 Hz, 7.2 A
 Cat. No. 11-690-626D 240V, 50/60 Hz, 5.1 A

Model 637D
 Cat. No. 11-690-637D 120V, 60 Hz, 7.2 A
 Cat. No. 11-690-638D 240V, 50/60 Hz, 5.1 A

Model 650D
 Cat. No. 11-690-650D 120V, 60 Hz, 7.7 A
 Cat. No. 11-690-651D 240V, 50/60 Hz, 5.4 A

Model	Power Requirements	Chamber Volumes
Model 625D	330 W	2.5 cu. Ft.
Model 637D	330 W	3.8 cu. Ft.
Model 650D	410W	5.0 cu. Ft.

Chamber Dimensions (W x D x H)

Model 625D 18 x 18 x 13.5 in.
 Model 637D 18 x 18 x 20 in.
 Model 650D 18 x 18 x 26.5 in.